

# Pearsonhydraulics

## Pearson Hydraulics Ltd part number - FQT4-###CLR

Construction: Strong, flexible and smooth non-toxic plasticized PVC.  
Shock resistant PVC spiral.  
Crushing, abrasion and weather resistant, light corrugated outside.

Application: For delivery of water, mineral water, milk, fruit juices, alimentary liquid etc.

Please contact our sales team on 01522 846846 should you not find the product or technical information you require on our website.

## Standard Duty Non-Toxic Delivery



ID		BP		VACUUM	BR/r	W	L
inch	mm	bar	psi	m/H <sub>2</sub> O	mm	g/m	m
3/4"	19	26	377	7	90	280	30/50
1"	25	24	348	6	110	350	30/50
	30	22	319	6	125	440	30/50
1 1/4"	32	21	305	6	130	460	30/50
	35	20	290	6	140	520	30/50
1 1/2"	38	19	276	6	155	570	30/50
	40	19	276	6	165	590	30/50
	45	19	276	6	195	670	30/50
2"	51	16	232	6	215	830	30/50
	55	15	218	6	225	880	30/50
	60	15	218	6	260	950	30/50
2 1/2 "	63	15	218	6	275	1000	30/50
	70	13	189	6	310	1150	30/50
3"	76	13	189	6	335	1450	30/50
	80	13	189	6	350	1530	20/30
	90	13	189	6	415	1750	20/30
4"	102	12	174	6	450	2150	20/30
	110	11	160	5	500	2450	20/30
	120	11	160	5	620	2900	20/30
5"	127	11	160	4	660	3200	20/30
6"	152	10	145	3	750	4200	20/30
8"	203	8	116	2	930	6400	10



- 5 °C / + 60 °C  
+23 °F / +140 °F